



GSS



GSX

- GSS Nail Wide Diameter: 2.7mm
- GSX Nail Designed for Steel Penetration: 3.0mm Diameter
- High Strength Steel Material
- Coated with White Mechanical Galvanization for Corrosion Resistance
- Nail Length Suitable for Every Application

Product	Art. No.	Body Diameter	Nail Length	Head Diameter	Qty Per Box	Qty Per Carton
GSS 16	32317	2,7	16	6,3	1000	5000
GSS 20	32312	2,7	20	6,3	1000	5000
GSS 25	32313	2,7	25	6,3	1000	5000
GSS 30	32314	2,7	30	6,3	1000	5000
GSS 35	32315	2,7	35	6,3	1000	5000
GSS 40	32316	2,7	40	6,3	1000	5000

Product	Art. No.	Body Diameter	Nail Length	Head Diameter	Qty Per Box	Qty Per Carton
GSX 15	32327	3	15	6,3	1000	5000
GSX 17	32321	3	17	6,3	1000	5000
GSX 19	32322	3	20	6,3	1000	5000
GSX 22	32323	3	25	6,3	1000	5000
GSX 27	32324	3	30	6,3	1000	5000
GSX 32	32325	3	35	6,3	1000	5000
GSX 40	32326	3	40	6,3	1000	5000

GSS-GSX

Concrete Nail

Main Material

- Concrete
- Steel
- Wood

Application Field

- Insulation
- Drywall
- Facades
- Steel profiles
- Warning sign boards
- Tunnel applications

GSS

Steel and High Grade

Concrete Nail

GSX

Steel and High Grade

Concrete Nail



Chemical Anchors

Heavy Duty Anchors

General Purpose Fasteners

Frame Anchors

Aerated Concrete Anchors

Drywall Anchors

Nailing Systems

Insulation Anchors

Screws

Drill Bits

Scaffold Fasteners

Solar System Fasteners

Special Fixing

